

PRODUCT DESCRIPTION

4075RLA® Conform Series® application tape is standard weight saturated paper coated with a high tack rubber adhesive designed specifically as a premasking of small and mid-sized die cut or prespaced vinyl and printed graphics. 4075RLA® features RLA® technology with improved adhesion to paper or film release liners.

| | |
|---|----------------------------------|
| Adhesive | Rubber-based |
| Color | White/Translucent |
| Caliper, facestock | 100-113 microns (4.0 -4.5 mils) |
| Caliper, facestock + adhesive | 125-138 microns (5.0 - 5.5 mils) |
| Adhesion to Stainless Steel | 18 – 20 N/100mm (16 – 18 oz.) |
| Tensile | 297 N/100mm (17lb./in) |
| Elongation | 3-4% |
| Tear Resistance (grams) | 50 |
| Shelf life Stored at 22°C (72°F)/ 50-55 % RH | 1 year |

FEATURES & BENEFITS

- Removes easily following graphics application.
- If adhesive touches adhesive, Conform pulls apart easily with no adhesive delamination.
- Works well in either wet or dry applications with no adhesive transfer.
- Available in factory-cut rolls with no damaged edges for trouble-free unwind.

APPLICATIONS

- Premask for small and medium size vinyl graphics .
- All-purpose application tape for wet and dry applications.
- Excellent for transferring graphics to banners.

Important notice: All RTape products are subject to continuous quality control throughout the manufacturing process and are warranted to be free from manufacturing defects. RTape stands behind its products and will replace or credit any defective material. Because RTape products are used for a variety of applications, the purchaser is responsible for determining the suitability and performance of this product for their specific purpose, prior to use and the purchaser shall assume all risks regarding such use.