



Substrate		DIN 60001	min. 80 % recycled polyester
Weave		DIN ISO 9354	woven fabric
Weight approx.		DIN EN ISO 2286-2	220 g/m <sup>2</sup>
Fire retardancy		DIN 4102 B1	yes
Application			indoor
Width		DIN EN ISO 2286-1	max. 310 cm / 122 inch (see overview)
Print side			width < 3 m: print side outside width > 3 m: print side inside
Roll length			30 ± 0,5 m; 50 ± 0,5 m (width 310 cm)
Type of ink			all kinds of solvent inks, UV-curable inks*, latex inks

www.dupli-data.fr

## Advantages

- matt surface
- canvas like fabric
- made of 100 % PET bottle recycled yarn
- trimming cold (no fraying)

## Applications

- banner
- frame tensioning systems
- art reproduction
- wall covering\*\*

\* please consider the risk of curling because UV-curable inks will still be hardening after a while  
 \*\* please test in advance; the adhesive behavior depends on the surface applied



All details are nominal values and are subject to change within usual tolerances (± 5 %). The information provided in this document is based on current knowledge and experience. They do not exempt a manufacturer/processor from carrying out their own tests and trials as their in-house handling and manufacturing processes can have a significant range of influences on outcomes. Application, utilisation and processing of products is taking place outside of our control and are therefore the sole responsibility of the manufacturer/processor. date: 01/2020